

AIR FILTRATION  
& AIR QUALITY



## HEPAGEL-129-ARL

Hepa Filters With Gel Gasket

### APPLICATIONS

- Used in systems made according to sealed with gel technique
- Clean rooms with LAF counters and operating rooms

### FILTER CODE STRUCTURE

Type	<b>HG</b>	HEPAGEL
Class EN 1822	<b>11</b>	E11
Frame	<b>A</b>	A: Aluminum
Media	<b>R</b>	R: Micro Glass Fibre
Pleat Depth	<b>L</b>	K: 48 mm    M: 58 mm N: 75 mm    L: 100 mm
Surface Grid	<b>2</b>	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	<b>G</b>	Gel Type
Gasket Direction	<b>G</b>	C: Air Outlet G: Air Inlet
Size	0610-0610-129	

### TECHNICAL SPECIFICATIONS

Class EN1822	E10	E11	E12	H13	H14	U15
Av. Efficiency EN1822	≥85%	≥95%	≥99.5%	≥99.95%	≥99.995%	≥99.9995%
Max. Temperature	80°C					
Relative Humidity	100 %					
Rec. Final Pres. Drop	600 Pa.					
Filter Stage	III - IV					

For more information please click here.

