



PREBAG-PR-600

Synthetic Rigid Pocket Filters

APPLICATIONS

- Conditioning, ventilation systems, power plants and turbo machines
- Used as pre-filter or second-stage filter
- Low start pressure drop
- High dust holding capacity
- Reduced operating costs
- Provides long service interval

FILTER CODE STRUCTURE

Type	PB	PREBAG-600
Class EN 779-2012 Class ISO COARSE	4	G4 COARSE>90
Frame	P	P : Plastic (Black) G : Galvanized T : Stainless Steel V : One piece plastic (25 mm)
Header Thickness	25	25 : 25 mm 20 : 20 mm
Media	R	R : Rigid
Pocket Number	08	8 : 8 Pockets 6 : 6 Pockets
Gasket Type	X	X : Without Gasket P : Polyurethane R : Rubber E : EPDM
Gasket Direction	X	X : No C : Air Outlet G : Air Inlet
Size		0592-0592-600

TECHNICAL SPECIFICATIONS

Class EN 779-2012	G4
Class ISO 16890-COARSE	>60
Av. Efficiency EN 779-2012	90%
Av. Efficiency ISO 16890	>60%
Max. Temperature	80°C
Relative Humidity	100 %
Rec. Final Pres. Drop	EN 779-2012 250 Pa. ISO 16890 200 Pa.
Filter Stage	I - II

For more information please click here. 